

## WATERMAKER BAHAMAS 3000 GPD

## **FACTS**

Compact, durable, and reliable solution for boats, Houses, Beaches, and other applications.

With a simple installation and easy operation procedure, this machine provides you with 3000 Gallons-Per-Day of drinkable water in any part of the open sea.

All components are in the same frame, including the feed pump (priming booster pump).



## **PRODUCT SPECIFICATIONS**

ITEM	BAHAMAS 3000GPD BASIC	BAHAMAS 3000GPD PREMIUM
Production Per Day	3000 Gallons	3000 Gallons
<b>Production Per Hour</b>	120 Gallons	120 Gallons
Power requirement	110V 1-Phase or 220V 1-Phase	110V 1-Phase or 220V 1-Phase
Dimensions	53"x24"x20"	53"x24"x20"
Weight	135 lbs.	135 lbs.
Controls	Analog controls – Manual Operation	Analog controls – Manual Operation
Salt Rejection	99.5%	99.5%
Membranes	(2) SW-4040 High salt rejection	(2) SW-4040 High salt rejection
Booster Pump	Priming Pump with Stainless Body	Priming Pump with Stainless Body
High-Pressure Pump	Piston Pump with Brass Body	Piston Pump with Stainless Body
Pre-Treatment	(1) 10"x2.5" 5-micron PP filter	(1) 10"x2.5" 5-micron PP filter
Pre-Treatment	(1) 10"x2.5" 1-micron PP filter	(1) 10"x2.5" 1-micron PP filter
After-Treatment	Ultraviolet Sterilizer 12W (Optional)	Ultraviolet Sterilizer 12W (Optional)
After-Treatment	Activated Carbon filter	Activated Carbon filter
Water Quality	Online Monitoring TDS	Online Monitoring TDS
Warranty	Tecnortham Standard Warranty (1 year)	Tecnortham Standard Warranty (1 year)