

WATERMAKERS

COMPACT PACIFIC 300GPD

FACTS

Compact, durable, and reliable solution for boaters with limited power and space options.

With a simple installation and easy operation procedure, this machine provides you with 300 Gallons-Per-Day of drinkable water in any part of the open sea.

All components are in the same frame, including the feed pump (priming booster pump).

PRODUCT SPECIFICATIONS



ITEM	PACIFIC 300PGD BASIC	PACIFIC 300PGD PREMIUM
Production / Day	300 Gallons	300 Gallons
Production / Hour	12 Gallons	12 Gallons
Power Requirement	110V 1 Phase or 220V 1 Phase	110V 1 Phase or 220V 1 Phase
Dimensions	24"x18"x18"	24"x18"x18"
Weight	90 lbs.	90 lbs.
Controls	Analog controls – Manual operation	Analog controls – Manual operation
Salt Rejection	99.5%	99.5%
Membranes	(1) SW-2521 High rejection	(1) SW-2521 High rejection
Booster Pump	Priming Pump with SS Body	Priming Pump with SS Body
High Pressure Pump	Piston Pump Brass Body	Piston Pump with SS Body (Stainless Steel)
Pre-Treatment	(1) 10"x2.5" 5-micron PP filter	(1) 10"x2.5" 5-micron PP filter
Pre-Treatment	(1) 10"x2.5" 1-micron PP filter	(1) 10"x2.5" 1-micron PP filter
After-Treatment	Ultraviolet Sterilizer 12W	Ultraviolet Sterilizer 12W
After-Treatment	Activated Carbon filter	Activated Carbon filter
Water Quality	Online Monitoring TDS	Online Monitoring TDS
Warranty	Tecnortham standard warranty	Tecnortham standard warranty