

WATERMAKERS

COMPACT ATLANTIC 600GPD

FACTS

Fully automatic system with PLC+IHM program, compact, durable, and reliable solution for boaters with limited power and space options.

It is simple installation and easy operation provides all water you need in any part of the open sea.

All components in the same frame, included the feed



PRODUCT SPECIFICATIONS

ITEM	ATLANTIC 600PGD BASIC	ATLANTIC 600PGD PREMIUM
Production / Day	600 gal	600 gal
Production / Hour	25 gal	25 gal
Power Requirement	110V 1 Phase or 220V 1 Phase	110V 1 Phase or 220V 1 Phase
Dimensions	24"x18"x18"	24"x18"x18"
Weight	100 lbs.	100 lbs.
Controls	Fully automatic system with PLC+IHM	Fully automatic system with PLC+IHM
Salt Rejection	99.5%	99.5%
Membrane	(2) SW-2521 High rejection	(2) SW-2521 High rejection
Booster Pump	Priming Pump SS Body	Priming Pump SS Body
Pressure Pump	Piston Pump Brass body	Piston Pump SS Body (Stainless Steel)
Pre-Treatment	(1) 10"x2.5" 5-micron PP filter	(1) 10"x2.5" 5-micron PP filter
Pre-Treatment	(1) 10"x2.5" 1-micron PP filter	(1) 10"x2.5" 1-micron PP filter
After-Treatment	Ultraviolet Sterilizer 12W	Ultraviolet Sterilizer 12W
After-Treatment	Activated Carbon filter	Activated Carbon filter
Water Quality	Online Monitoring TDS	Online Monitoring TDS
Warranty	Tecnortham std warranty	Tecnortham std warranty